



TECHNICAL DATA

- Size : DN50-DN65
- Maximum working temperature : -10 / +80°C
- Inlet pressure : 7- 16 bar
- Adjustable outlet pressure : 3.5- 4.5 bar

* For inlet pressure or outlet pressure other, please indicate clearly on the inquiry or order list.

APPLICATION

Fire- fighting systems.

SPECIFICATION

- Type: Pressure reducing angle valve
- Connection end: Threaded ISO 228-1
- Connect with hose by Adapter
- Painting: Red colour
- Operation: Handwheel

MATERIALS

No.	Parts name	Material
1	Body	Ductile iron
2	Seat	Brass
3	Dics	Ductile iron + NBR
4	Pin	Stainless steel
5	Stem	Stainless steel
6	Screw	Steel
7	Stem nut	Brass
8	Bonnet	Ductile iron
9	Handwheel	Ductile iron
10	Bolt	Steel
11	O-ring	Rubber
12	O-ring	Rubber
13	Plate	Brass

No.	Parts name	Material
14	Spring	Stainless steel
15	Fitting	Brass
16	Adapter	Aluminium

DIMENSIONS

DN	L	d1	d3	d4	Hc	Ho	h	D
50	95	43	77	84	160	185	65	95
65	100	57	93	102	180	195	75	95